ASSOCIATION CONNECTIN	Material Composit © Copyright 2005. IPC, I international and Pan-Am	Bannockb	urn, Illinois. A	ll rights reserved utions.	under both	This docume level parts, th	ent is a decla he declaration	aration of on enco	of the substances mpasses all lowe	within er level i	the manufactu naterials for w	rer listed it which the m	tem. N nanufa	lote: if th cturer ha	e item is an as s engineering	sembly with lower responsibility.
1752-21.1					Form Type ³ Distribute						ials and M	ials and Mfg Information				
Supplier Inform	ation															
Company name*			Company unique ID			Unique ID Authority					Respons	Response Date*				
onsemi										2024-05-	2024-05-18					
Contact Name	Title - Contact			1	Phone - Contact*					Email -	Email - Contact*					
Product-Env-Stewa	rds	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*					Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com					
Requeste	Requester Item Number Mfr Item NCP4305			Number Mfr Item Name			Effective Date Version Manufacturing Sit		cturing Site	Weight*		ıt*	UOM	Unit Type		
				DMTTWG Secondary Side Synchronous Rectification Driver for High Efficiency SMPS Topologies			2024-05-18	05-18 MY1		8.51			mg	Each		
Manufacturing	Proccess Information	l														
Terminal	Terminal Plating / Grid Array Material			erminal Base Alloy J-STD		Rating	Peak F	Peak Process Body Temperature		re Max Time at Peak Temper		Temperat	rature Number of Reflow Cycles		les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		С	30 sec		secon	seconds 3			
Comments									ł			-				
evel 1 - maximum t	ime at peak temperature d	uring sol	dering is 10-3	0 seconds												
for more information	on regarding material com	position p	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.85	mg	Supplier	Silicon (Si)	7440-21-3		0.85	mg
Die Attach Tape	0.09	mg		Epoxy resin	proprietary data		0.036	mg
			Supplier	Acrylic resins	Proprietary Data		0.054	mg
Lead Frame	2.86	mg	Supplier	Tin (Sn)	7440-31-5		0.0071	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0063	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0071	mg
			Supplier	Copper (Cu)	7440-50-8		2.8394	mg
Mold Compound-Black	4.52	mg	Supplier	Epoxy and Phenolic Resin	40216-08-8		0.3616	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0226	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.0904	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.9098	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1356	mg
Plating	0.1	mg	Supplier	Palladium (Pd)	7440-05-3		0.0024	mg
			В	Nickel (Ni)	7440-02-0		0.088	mg
			Supplier	Gold (Au)	7440-57-5		0.0096	mg
Vire Bond - Au	0.09	mg	Supplier	Gold (Au)	7440-57-5		0.09	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).