



Title of Change:	Copper wire conversion for LA72900VA		
Proposed first ship date:	3 March 2017		
Contact information:	Contact your local ON Semiconductor Sales Office or <Hiroshi.Kojima@onsemi.com> <kenya.liguchi@onsemi.com> or <Hidekazu.Inoue@onsemi.com>		
Samples:	Contact your local ON Semiconductor Sales Office		
Additional Reliability Data:	Contact your local ON Semiconductor Sales Office or <Satoru.Fujinuma@onsemi.com>		
Type of notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <PCN.Support@onsemi.com>.		
Change Part Identification:	Affected products will be identified with date code.		
Change category:	☐ Wafer Fab Change ☒ Assembly Change ☐ Test Change ☐ Other _____		
Change Sub-Category(s):	☐ Manufacturing Site Change/Addition ☒ Material Change ☐ Datasheet/Product Doc change ☐ Manufacturing Process Change ☐ Product specific change ☐ Shipping/Packaging/Marking ☐ Other: _____		
Sites Affected:	☐ All site(s) ☐ not applicable ☒ ON Semiconductor site(s) : ON Tarlac City, Philippines ☐ External Foundry/Subcon site(s)		
Description and Purpose:			
This Process Change Notification is to notify customers of the following change:			
• Gold wire connecting chip and Lead will be changed to Copper wire • Mold resin will be changed to be suitable for Copper wire.			
	Before Change Description	After Change Description	
Wire material	Au	Cu	
Mold Compound	Epoxy(A)	Epoxy(B)	
Halide free	No	Yes	
There is no change to the electrical characteristic performance for the affected products.			

**Reliability Data Summary:**

QV DEVICE NAME : LA72900VA-TLM-E

PACKAGE : SSOP24(225mil)

Test	Specification	Condition	Interval	Results
HTOL	EIAJ ED-4701/100	Tj=Tjmax, Vcc=Operatingmax	1000 hrs	0/22
THB*	EIAJ ED-4701/100	85°C, 85% RH, Vcc=recommended	1000 hrs	0/22
TC*	EIAJ ED-4701/100	Ta= -65°C to +150°C	100 cyc	0/22
AC*	EIAJ ED-4701-3	Ta=121°C ,RH=100% ,205kPa	50 hrs	0/22
HTSL	EIAJ ED-4701/200	Ta= 150°C	1000 hrs	0/22
RSH	EIAJ ED-4701/300	Ta = 255°C , 10 sec (peak 260°C)	2times	0/22

Note:

The test items with * mark are put into operation after the reflow soldering (at 255°C for 10seconds)

Electrical Characteristic Summary:

There is no change in the electrical performance. Datasheet specifications remain unchanged.

List of affected Standard Parts:

Part Number	Qualification Vehicle
LA72900VA-TLM-E	LA72900VA-TLM-E