

Final Product/Process Change Notification Document #:FPCN26435X

Issue Date:20 Dec 2024

Title of Change:	Qualification of SiC Mosfet M3S 1200V 200mm in onsemi Bucheon, Korea.		
Proposed First Ship date:	31 Mar 2025 or earlier if approved by customer		
Contact Information:	Contact your local onsemi Sales Office.		
PCN Samples Contact:	Contact your local onsemi Sales Office. Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.		
Additional Reliability Data:	Contact your local onsemi Sales Office.		
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. onsemi will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com		
Marking of Parts/ Traceability of Change:	Change material can be identified by date code or lot code		
Change Category:	Wafer Fab Change		
Change Sub-Category(s):	Manufacturing Process	Manufacturing Process Change	
Sites Affected:			
onsemi Sites		External Foundry/Subcon Sites	
onsemi Bucheon, Korea		None	

Description and Purpose:

This Final Change Notification (FPCN) is to notify customers of the qualification of SiC MOSFET M3S 1200V 200mm in onsemi Bucheon, Korea.

This transfer enables expanded capacity for this technology and ensures business continuity.

	Before Change Description	After Change Description	
FAB Site	onsemi Bucheon, Korea	onsemi Bucheon, Korea	
Probe Site	onsemi Bucheon, Korea	onsemi Bucheon, Korea	
Wafer size	150mm	150mm & 200mm	

There is no product marking change as a result of this change

TEM001793 Rev. F Page 1 of 2



Final Product/Process Change Notification

Document #:FPCN26435X Issue Date:20 Dec 2024

Reliability Data Summary:

QV DEVICE NAME : NTH4L022N120M3S

RMS : 100019 / 100615 / 100759 / 100761

PACKAGE: TO247-4L

Test	Specification	Condition	Interval	Results
High Temperature Reverse Bias	JESD22-A108	Tj=175°C, 100% max rated V(1200V)	1008hrs	0/240
High Temperature Gate Bias+	JESD22-A108	Tj=175°C, 100% max rated Vgss(22V)	1008hrs	0/240
High Temperature Gate Bias-	JESD22-A108	Tj=175°C, 100% min rated Vgss(-10V)	1008hrs	0/240
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008hrs	0/240
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 5 min	6000 cyc	0/240
Temperature Cycling	JESD22-A104	Ta= -55°C to +175°C	1000сус	0/240
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, 80% rated V(960V)	1008hrs	0/240
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs	0/240
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec Required for through hole devices only		0/30
Solderability	JSTD002	Ta = 245°C, 5 sec		0/ 15
Physical Dimensions	JESD22-B120			

Electrical Characteristics Summary:

Electrical characteristics are not impacted.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Part Number	Qualification Vehicle	
NTHL022N120M3S	NTH4L022N120M3S	
NTH4L022N120M3S	NTH4L022N120M3S	

TEM001793 Rev. F Page 2 of 2