



## Final Product/Process Change Notification

Document #:FPCN25572X24

Issue Date: 13 Feb 2024

<b>Title of Change:</b>	Update to <b>FPCN25572X</b> - To include the reliability data of 3V Minigates in SOT553 for the Qualification of Vanguard Fab and Assembly related changes for Logic parts.	
<b>Proposed First Ship date:</b>	20 May 2024 or earlier if approved by customer	
<b>Contact Information:</b>	Contact your local onsemi Sales Office or <a href="mailto:logic.fpcn@onsemi.com">logic.fpcn@onsemi.com</a>	
<b>PCN Samples Contact:</b>	Contact your local onsemi Sales Office. Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.	
<b>Additional Reliability Data:</b>	Contact your local onsemi Sales Office or <a href="mailto:ChangKit.Mok@onsemi.com">ChangKit.Mok@onsemi.com</a>	
<b>Type of Notification:</b>	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. onsemi will consider this change accepted unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <a href="mailto:PCN.Support@onsemi.com">PCN.Support@onsemi.com</a>	
<b>Marking of Parts/ Traceability of Change:</b>	Custom source on label will show TW instead of US/JP to indicate new die source from Vanguard. Changed material may be identified by plant code or lot code too.	
<b>Change Category:</b>	Wafer Fab Change, Assembly Change, Test Change	
<b>Change Sub-Category(s):</b>	Manufacturing Site Transfer, Datasheet/Product Doc change	
<b>Sites Affected:</b>		
<b>onsemi Sites</b>	<b>External Foundry/Subcon Sites</b>	
onsemi Leshan, China	Vanguard International Semiconductor, Taiwan	
<b>Description and Purpose:</b>		
With reference to <b>FPCN25572X</b> , this FPCN presents the updated reliability results for 3V Minigates SOT553.		
	<b>From</b>	<b>To</b>
<b>Fab Site</b>	Tower	Vanguard
<b>Wafer Diameter</b>	6 inch	8 inch
<b>Bond Wire</b>	Au	Cu
<b>Mold Compound</b>	Showa Denko GE200F	Hysol GR640 HV

## Datasheet Changes:

### SL17SGxx/NL17SGxx Family

## SL17SG125 – Max Ratings and Recommended Operating Conditions

### Existing

MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V <sub>CC</sub>	DC Supply Voltage	-0.5 to +5.5	V
V <sub>IN</sub>	DC Input Voltage	-0.5 to +4.6	V
V <sub>OUT</sub>	DC Output Voltage Output at High or Low State Power-Down Mode (V <sub>CC</sub> = 0 V)	-0.5 to V <sub>CC</sub> + 0.5 -0.5 to +4.6	V
I <sub>IK</sub>	DC Input Diode Current V <sub>IN</sub> < GND	-20	mA
I <sub>OK</sub>	DC Output Diode Current V <sub>OUT</sub> < GND	-20	mA
I <sub>OUT</sub>	DC Output Source/Sink Current	±20	mA
I <sub>CC</sub>	DC Supply Current per Supply Pin	±20	mA
I <sub>GND</sub>	DC Ground Current per Ground Pin	±20	mA
T <sub>STG</sub>	Storage Temperature Range	-65 to +150	°C
T <sub>L</sub>	Lead Temperature, 1 mm from Case for 10 Seconds	260	°C
T <sub>J</sub>	Junction Temperature Under Bias	+150	°C
MSL	Moisture Sensitivity	Level 1	
FR	Flammability Rating Oxygen Index: 28 to 34	UL 94 V-0 @ 0.125 in	
V <sub>ESD</sub>	ESD Withstand Voltage Human Body Model (Note 2) Machine Model (Note 3)	>2000 >100	V
I <sub>LATCHUP</sub>	Latchup Performance Above V <sub>CC</sub> and Below GND at 125°C (Note 4)	±100	mA

RECOMMENDED OPERATING CONDITIONS

Symbol	Characteristics	Min	Max	Unit
V <sub>CC</sub>	Positive DC Supply Voltage	0.9	3.6	V
V <sub>IN</sub>	Digital Input Voltage	0.0	3.6	V
V <sub>OUT</sub>	Output Voltage Output at High or Low State Power-Down Mode (V <sub>CC</sub> = 0 V)	0.0 0.0	V <sub>CC</sub> 3.6	V
T <sub>A</sub>	Operating Temperature Range	-55	+125	°C
Δt / ΔV	Input Transition Rise or Fall Rate V <sub>CC</sub> = 3.3 V ± 0.3 V	0	200	ns/V

### New

Table 1. MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V <sub>CC</sub>	DC Supply Voltage	-0.5 to +4.3	V
V <sub>IN</sub>	DC Input Voltage	-0.5 to +4.3	V
V <sub>OUT</sub>	DC Output Voltage Active-Mode (High or Low State) Tri-State Mode (Note 1) Power-Down Mode (V <sub>CC</sub> = 0 V)	-0.5 to V <sub>CC</sub> + 0.5 -0.5 to +4.3 -0.5 to +4.3	V
I <sub>IK</sub>	DC Input Diode Current V <sub>IN</sub> < GND	-20	mA
I <sub>OK</sub>	DC Output Diode Current V <sub>OUT</sub> < GND	-20	mA
I <sub>OUT</sub>	DC Output Source/Sink Current	±20	mA
I <sub>CC</sub> or I <sub>GND</sub>	DC Supply Current Per Supply Pin or Ground Pin	±20	mA
T <sub>STG</sub>	Storage Temperature Range	-65 to +150	°C
T <sub>L</sub>	Lead Temperature, 1 mm from Case for 10 Seconds	260	°C
T <sub>J</sub>	Junction Temperature Under Bias	+150	°C
θ <sub>JA</sub>	Thermal Resistance (Note 2)	SC-88A SOT-963 UDFN6 377 254 154	°C/W
P <sub>D</sub>	Power Dissipation in Still Air at 85°C	SC-88A SOT-963 UDFN6 332 491 812	mW
MSL	Moisture Sensitivity	Level 1	
FR	Flammability Rating	Oxygen Index: 28 to 34 UL 94 V-0 @ 0.125 in	
V <sub>ESD</sub>	ESD Withstand Voltage (Note 3)	Human Body Model Charged Device Model 2000 1000	V
I <sub>LATCHUP</sub>	Latchup Performance (Note 4)	±100	mA

RECOMMENDED OPERATING CONDITIONS

Symbol	Characteristics	Min	Max	Unit
V <sub>CC</sub>	Positive DC Supply Voltage	0.9	3.6	V
V <sub>IN</sub>	Digital Input Voltage	0.0	3.6	V
V <sub>OUT</sub>	Output Voltage Output at High or Low State Power-Down Mode (V <sub>CC</sub> = 0 V)	0.0 0.0	V <sub>CC</sub> 3.6	V
T <sub>A</sub>	Operating Temperature Range	-55	+125	°C
Δt / ΔV	Input Transition Rise or Fall Rate V <sub>CC</sub> = 3.3 V ± 0.3 V	0	10	ns/V

## S/NL17SG125 – DC Characteristics

### Existing

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C		T <sub>A</sub> = -55°C to +125°C		Unit
				Min	Max	Min	Max	
V <sub>IH</sub>	High-Level Input Voltage		0.9	V <sub>CC</sub>		V <sub>CC</sub>		V
			1.1 to 1.3	0.7V <sub>CC</sub>		0.7V <sub>CC</sub>		
			1.4 to 1.6	0.65V <sub>CC</sub>		0.65V <sub>CC</sub>		
			1.65 to 1.95	0.65V <sub>CC</sub>		0.65V <sub>CC</sub>		
			2.3 to 2.7	1.7		1.7		
V <sub>IL</sub>	Low-Level Input Voltage		3.0 to 3.6	2.0		2.0		V
			0.9		GND		GND	
			1.1 to 1.3		0.3V <sub>CC</sub>		0.3V <sub>CC</sub>	
			1.4 to 1.6		0.35V <sub>CC</sub>		0.35V <sub>CC</sub>	
			1.65 to 1.95		0.35V <sub>CC</sub>		0.35V <sub>CC</sub>	
V <sub>OH</sub>	High-Level Output Voltage	V <sub>IH</sub> = V <sub>IH</sub> or V <sub>IL</sub> I <sub>OH</sub> = -20 µA I <sub>OH</sub> = -0.3 mA I <sub>OH</sub> = -1.7 mA I <sub>OH</sub> = -3.0 mA I <sub>OH</sub> = -4.0 mA I <sub>OH</sub> = -8.0 mA	0.9	0.75		0.75		V
			1.1 to 1.3	0.75V <sub>CC</sub>		0.75V <sub>CC</sub>		
			1.4 to 1.6	0.75V <sub>CC</sub>		0.75V <sub>CC</sub>		
			1.65 to 1.95	V <sub>CC</sub> -0.45		V <sub>CC</sub> -0.45		
			2.3 to 2.7	2.0		2.0		
V <sub>OL</sub>	Low-Level Output Voltage	V <sub>IH</sub> = V <sub>IH</sub> or V <sub>IL</sub> I <sub>OL</sub> = 20 µA I <sub>OL</sub> = 0.3 mA I <sub>OL</sub> = 1.7 mA I <sub>OL</sub> = 3.0 mA I <sub>OL</sub> = 4.0 mA I <sub>OL</sub> = 8.0 mA	3.0 to 3.6	2.48		2.48		V
			0.9		0.1		0.1	
			1.1 to 1.3		0.25V <sub>CC</sub>		0.25V <sub>CC</sub>	
			1.4 to 1.6		0.25V <sub>CC</sub>		0.25V <sub>CC</sub>	
			1.65 to 1.95		0.45		0.45	
I <sub>IN</sub>	Input Leakage Current	0 ≤ V <sub>IN</sub> ≤ 3.6 V	0 to 3.6		±0.1		±1.0	µA
I <sub>CC</sub>	Quiescent Supply Current	V <sub>IN</sub> = V <sub>CC</sub> or GND	3.6		0.5		10.0	µA

### New

Table 3. DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C		T <sub>A</sub> = -55°C to +125°C		Unit
				Min	Max	Min	Max	
V <sub>IH</sub>	High-Level Input Voltage		0.9	-	V <sub>CC</sub>	-	-	V
			1.1 to 1.3	0.7 × V <sub>CC</sub>	-	-	0.7 × V <sub>CC</sub>	
			1.4 to 1.6	0.65 × V <sub>CC</sub>	-	-	0.65 × V <sub>CC</sub>	
			1.65 to 1.95	0.65 × V <sub>CC</sub>	-	-	0.65 × V <sub>CC</sub>	
			2.3 to 2.7	1.7	-	-	1.7	
V <sub>IL</sub>	Low-Level Input Voltage		3.0 to 3.6	2.0	-	-	2.0	V
			0.9	-	GND	-	-	
			1.1 to 1.3	-	0.3 × V <sub>CC</sub>	-	0.3 × V <sub>CC</sub>	
			1.4 to 1.6	-	0.35 × V <sub>CC</sub>	-	0.35 × V <sub>CC</sub>	
			1.65 to 1.95	-	0.35 × V <sub>CC</sub>	-	0.35 × V <sub>CC</sub>	
V <sub>OH</sub>	High-Level Output Voltage	V <sub>IH</sub> = V <sub>IH</sub> or V <sub>IL</sub> I <sub>OH</sub> = -20 µA I <sub>OH</sub> = -0.3 mA I <sub>OH</sub> = -1.7 mA I <sub>OH</sub> = -3.0 mA I <sub>OH</sub> = -4.0 mA I <sub>OH</sub> = -8.0 mA	0.9	-	0.75	-	-	V
			1.1 to 1.3	-	0.75 × V <sub>CC</sub>	-	0.75 × V <sub>CC</sub>	
			1.4 to 1.6	-	0.75 × V <sub>CC</sub>	-	0.75 × V <sub>CC</sub>	
			1.65 to 1.95	-	V <sub>CC</sub> - 0.45	-	V <sub>CC</sub> - 0.45	
			2.3 to 2.7	-	2.0	-	2.0	
V <sub>OL</sub>	Low-Level Output Voltage	V <sub>IH</sub> = V <sub>IH</sub> or V <sub>IL</sub> I <sub>OL</sub> = 20 µA I <sub>OL</sub> = 0.3 mA I <sub>OL</sub> = 1.7 mA I <sub>OL</sub> = 3.0 mA I <sub>OL</sub> = 4.0 mA I <sub>OL</sub> = 8.0 mA	3.0 to 3.6	-	2.48	-	2.48	V
			0.9	-	0.1	-	-	
			1.1 to 1.3	-	0.25 × V <sub>CC</sub>	-	0.25 × V <sub>CC</sub>	
			1.4 to 1.6	-	0.25 × V <sub>CC</sub>	-	0.25 × V <sub>CC</sub>	
			1.65 to 1.95	-	0.45	-	0.45	
I <sub>IN</sub>	Input Leakage Current	V <sub>IN</sub> = 0 V to 3.6 V	0.9 to 3.6	-	±0.1	-	±1.0	µA
I <sub>OFF</sub>	Power Off Leakage Current	V <sub>IN</sub> = 0 V to 3.6 V V <sub>OUT</sub> = 0 V to 3.6 V	0	-	-	-	10.0	µA
I <sub>CC</sub>	Quiescent Supply Current	V <sub>IN</sub> = V <sub>CC</sub> or GND	0.9 to 3.6	-	-	-	10.0	µA

## S/NL17SG125 - AC Characteristics 1/3

### Existing

AC ELECTRICAL CHARACTERISTICS (Input t<sub>r</sub> = t<sub>f</sub> = 3.0 ns)

Symbol	Parameter	Test Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25 °C			T <sub>A</sub> = -55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y	C <sub>L</sub> = 10 pF, R <sub>L</sub> = 1 MΩ	0.9	-	11.3	13.6	-	15.9	ns
			1.1 to 1.3	-	8.3	10.4	-	12.8	
			1.4 to 1.6	-	5.0	8.5	-	10.0	
			1.65 to 1.95	-	4.0	6.2	-	6.7	
			2.3 to 2.7	-	2.6	3.9	-	4.4	
			3.0 to 3.6	-	2.1	3.1	-	3.7	
		C <sub>L</sub> = 15 pF, R <sub>L</sub> = 1 MΩ	0.9	-	12.6	14.7	-	17.0	ns
			1.1 to 1.3	-	9.6	11.5	-	15.2	
			1.4 to 1.6	-	5.6	9.3	-	11.2	
			1.65 to 1.95	-	4.5	6.9	-	7.1	
			2.3 to 2.7	-	2.9	4.4	-	5.0	
			3.0 to 3.6	-	2.4	3.4	-	3.9	
		C <sub>L</sub> = 30 pF, R <sub>L</sub> = 1 MΩ	0.9	-	14.5	16.3	-	19.6	ns
			1.1 to 1.3	-	11.3	13.6	-	17.5	
			1.4 to 1.6	-	8.2	13.1	-	15.9	
			1.65 to 1.95	-	6	9.2	-	9.6	
			2.3 to 2.7	-	4	5.7	-	6.1	
			3.0 to 3.6	-	3.3	4.4	-	4.8	

### New

AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25 °C			T <sub>A</sub> = -55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y	C <sub>L</sub> = 10 pF, R <sub>L</sub> = 1 MΩ	0.9	-	44.4	-	-	-	ns
			1.1 to 1.3	-	10.8	29.2	-	33.9	
			1.4 to 1.6	-	5.0	8.5	-	10.0	
			1.65 to 1.95	-	4.0	6.2	-	6.7	
			2.3 to 2.7	-	2.6	3.9	-	4.4	
			3.0 to 3.6	-	2.1	3.1	-	3.7	
		C <sub>L</sub> = 15 pF, R <sub>L</sub> = 1 MΩ	0.9	-	44.9	-	-	-	ns
			1.1 to 1.3	-	11.0	29.9	-	34.7	
			1.4 to 1.6	-	5.6	9.3	-	11.2	
			1.65 to 1.95	-	4.5	6.9	-	7.1	
			2.3 to 2.7	-	2.9	4.4	-	5.0	
			3.0 to 3.6	-	2.4	3.4	-	3.9	
		C <sub>L</sub> = 30 pF, R <sub>L</sub> = 1 MΩ	0.9	-	46.2	-	-	-	ns
			1.1 to 1.3	-	11.6	32.0	-	37.1	
			1.4 to 1.6	-	8.2	13.1	-	15.9	
			1.65 to 1.95	-	6	9.2	-	9.6	
			2.3 to 2.7	-	4	5.7	-	6.1	
			3.0 to 3.6	-	3.3	4.4	-	4.8	

## S/NL17SG125 - AC Characteristics 2/3

### Existing

$t_{PHZ}$ $t_{PLZ}$	Output Enable Time, OE to Y	$C_L = 10$ pF					
		$R_L = 100$ k $\Omega$	0.9	-	11.0	13.3	- 15.8
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	8.4	10.9	- 13.0
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	5.3	7.8	- 8.3
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	3.9	5.5	- 5.9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	2.5	3.5	- 3.8
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.1	2.7	- 3
		$C_L = 15$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	12.0	14.8	- 17.0
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	9.0	11.7	- 13.8
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	5.9	8.9	- 11
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	4.4	6.3	- 6.5
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	2.9	3.9	- 4.2
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.3	3	- 3.3
		$C_L = 30$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	13.0	15.2	- 18.3
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	10.0	13.1	- 15.2
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	8.3	12.2	- 13.7
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	6.1	8.6	- 9.7
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	3.8	5	- 5.5
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.9	3.8	- 4.2

### New

$t_{PHZ}$ $t_{PLZ}$	Output Enable Time, OE to Y	$C_L = 10$ pF					
		$R_L = 100$ k $\Omega$	0.9	-	43.3	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	10.5	29.0	- 33.7
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	5.3	7.8	- 8.3
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	3.9	5.5	- 5.9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	2.5	3.5	- 3.8
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.1	2.7	- 3
		$C_L = 15$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	43.8	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	10.7	29.9	- 34.5
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	5.9	8.9	- 11
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	4.4	6.3	- 6.5
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	2.9	3.9	- 4.2
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.3	3	- 3.3
		$C_L = 30$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	45.1	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	11.2	31.8	- 36.9
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	8.3	12.2	- 13.7
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	6.1	8.6	- 9.7
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	3.8	5	- 5.5
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	2.9	3.8	- 4.2

## S/NL17SG125 - AC Characteristics 3/3

### Existing

$t_{PHZ}$ $t_{PLZ}$	Output Disable Time, OE to Y	$C_L = 10$ pF					
		$R_L = 100$ k $\Omega$	0.9	-	100.4	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	9.1	14.4	- 22.4
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	7.1	9.1	- 10.4
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	6.5	8.3	- 9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	5.8	7.3	- 8.8
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	5.4	6.9	- 7.8
		$C_L = 15$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	122.2	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	9.8	15.3	- 25.1
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	7.8	9.8	- 11.3
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	7.2	9.2	- 10.6
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	7	8.2	- 10.3
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	6.6	7.7	- 9.5
		$C_L = 30$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	217.1	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	13.2	19.6	- 31.9
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	12.2	13.5	- 14.9
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	11.4	12.7	- 13.9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	11.3	12.2	- 13.5
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	10.2	11.5	- 12.9

### New

$t_{PHZ}$ $t_{PLZ}$	Output Disable Time, OE to Y	$C_L = 10$ pF					
		$R_L = 100$ k $\Omega$	0.9	-	89.6	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	9.1	16.5	- 22.4
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	7.1	9.1	- 10.4
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	6.5	8.3	- 9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	5.8	7.3	- 8.8
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	5.4	10.1	- 10.3
		$C_L = 15$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	117.8	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	9.8	18.4	- 25.1
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	7.8	9.8	- 11.3
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	7.2	9.2	- 10.6
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	7	8.2	- 10.3
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	6.6	11.1	- 11.3
		$C_L = 30$ pF					ns
		$R_L = 100$ k $\Omega$	0.9	-	202.1	-	-
		$R_L = 5$ k $\Omega$	1.1 to 1.3	-	13.2	24.3	- 31.9
		$R_L = 5$ k $\Omega$	1.4 to 1.6	-	12.2	13.5	- 14.9
		$R_L = 5$ k $\Omega$	1.65 to 1.95	-	11.4	12.7	- 13.9
		$R_L = 5$ k $\Omega$	2.3 to 2.7	-	11.3	12.2	- 13.5
		$R_L = 5$ k $\Omega$	3.0 to 3.6	-	10.2	14.8	- 15.1

**NL17SVxx Family**

## NL17SV16 - AC Characteristics

### Existing

AC ELECTRICAL CHARACTERISTICS									
Symbol	Parameter	Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C			T <sub>A</sub> = -55°C to -125°C		
				Min	Typ	Max	Min	Max	Unit
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y (Figures 3 and 4)	R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF	0.9	-	13.5	-	-	-	ns
		R <sub>L</sub> = 2 kΩ, C <sub>L</sub> = 15 pF	1.1 to 1.3	-	5.9	13.0	-	16.9	
		R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 30 pF	1.4 to 1.6	-	3.2	6.1	-	7.0	
			1.65 to 1.95	-	2.3	5.2	-	6.2	
			2.3 to 2.7	-	1.7	3.7	-	4.4	
			2.7 to 3.6	-	1.4	3.3	-	3.8	

### New

AC ELECTRICAL CHARACTERISTICS									
Symbol	Parameter	Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C			T <sub>A</sub> = -55°C to -125°C		
				Min	Typ	Max	Min	Max	Unit
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y (Figures 3 and 4)	R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF	0.9	-	18.49	-	-	-	ns
		R <sub>L</sub> = 2 kΩ, C <sub>L</sub> = 15 pF	1.1 to 1.3	-	5.4	13.0	-	16.9	
		R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 30 pF	1.4 to 1.6	-	3.2	6.1	-	7.0	
			1.65 to 1.95	-	2.3	5.2	-	6.2	
			2.3 to 2.7	-	1.7	3.7	-	4.4	
			2.7 to 3.6	-	1.4	3.3	-	3.8	

## NL17SV08 - AC Characteristics

### Existing

AC ELECTRICAL CHARACTERISTICS									
Symbol	Parameter	Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C			T <sub>A</sub> = -40°C to +85°C		
				Min	Typ	Max	Min	Max	Unit
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y (Figures 3 and 4)	R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF	0.9	-	15.9	-	-	-	ns
		R <sub>L</sub> = 2 kΩ, C <sub>L</sub> = 15 pF	1.1 to 1.3	-	6.8	11.6	-	14.6	
		R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 30 pF	1.4 to 1.6	-	3.6	6.0	-	7.2	
			1.65 to 1.95	-	2.6	4.5	-	5.3	
			2.3 to 2.7	-	1.9	2.6	-	3.7	
			2.7 to 3.6	-	1.6	2.3	-	3.0	

### New

AC ELECTRICAL CHARACTERISTICS									
Symbol	Parameter	Condition	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C			T <sub>A</sub> = -40°C to +85°C		
				Min	Typ	Max	Min	Max	Unit
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay, A to Y (Figures 3 and 4)	R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF	0.9	-	18.31	-	-	-	ns
		R <sub>L</sub> = 2 kΩ, C <sub>L</sub> = 15 pF	1.1 to 1.3	-	5.8	13.5	-	16.1	
		R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 30 pF	1.4 to 1.6	-	3.6	6.0	-	7.2	
			1.65 to 1.95	-	2.6	4.5	-	5.3	
			2.3 to 2.7	-	1.9	2.6	-	3.7	
			2.7 to 3.6	-	1.6	2.3	-	3.0	

**NL17SV32 - AC Characteristics - No changes.**



## Reliability Data Summary:

**QV DEVICE NAME:** NC7SP14P5X

**RMS:** S88008 / S88413

**PACKAGE:** SC88A

Test	Specification	Condition	Interval	Results
High Temperature Operating Life	JESD22-A108	Ta=125°C, 100 % max rated Vcc	1008 hours	0/231
Earlier Life Failure Rate	JESD22-A108	Ta=125°C, 100 % max rated Vcc	48 hours	0/2400
High Temperature Storage Life	JESD22-A103	Ta= 150°C	1008 hours	0/231
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260°C, Pre TC, uHAST, HAST for surface mount pkgs only	-	0/693
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C	500 cycles	0/231
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hours	0/231
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hours	0/231
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	-	0/30

**QV DEVICE NAME:** NL17SV16XV5T2G

**RMS:** S88114

**PACKAGE:** SOT553

Test	Specification	Condition	Interval	Results
High Temperature Operating Life	JESD22-A108	Ta=125°C, 100 % max rated Vcc	1008 hours	0/77
High Temperature Storage Life	JESD22-A103	Ta= 150°C	1008 hours	0/77
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260°C, Pre TC, uHAST, HAST for surface mount pkgs only	-	0/231
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C	500 cycles	0/77
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hours	0/77
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hours	0/77
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	-	0/10

## Electrical Characteristics Summary:

Electrical characteristics available upon request.

## List of Affected Parts:

**Note:** Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Part Number	Qualification Vehicle
NL17SV32XV5T2G	NC7SP14P5X, NL17SV16XV5T2G
NL17SV16XV5T2G	NC7SP14P5X, NL17SV16XV5T2G
NL17SV08XV5T2G	NC7SP14P5X, NL17SV16XV5T2G
SL17SG125XV5T2G	NC7SP14P5X, NL17SV16XV5T2G