



FINAL PRODUCT/PROCESS CHANGE NOTIFICATION # 16790ECGeneric Copy

Issue Date: 14-Feb-2013

TITLE: Final PCN for wafer fab transfer from Gifu in Japan to the waferfab Advanced Microelectronic Products, Inc(AMPI)(Group EC).

PROPOSED FIRST SHIP DATE: starting on 14-May-2013 until 3-Jun-2013 (the actual ship date will be different by each product, please check the responsible Sales person).

AFFECTED CHANGE CATEGORY(S): Wafer Fabrication Location Change

FOR ANY QUESTIONS CONCERNING THIS NOTIFICATION:

Contact your local ON Semiconductor Sales Office or Toshikazu.Hirai@onsemi.com

SAMPLES: Contact your local ON Semiconductor Sales Office or Katsuya.Ito@onsemi.com

ADDITIONAL RELIABILITY DATA: May be available

Contact your local ON Semiconductor Sales Office or Yasuhiro.Igarashi@onsemi.com.

NOTIFICATION TYPE:

Final Product/Process Change Notification (FPCN)

Final change notification sent to customers. FPCNs are issued at least 90 days prior to implementation of the change.

ON Semiconductor will consider this change approved unless specific conditions of acceptance are provided in writing within 30 days of receipt of this notice. To do so, contact <quality@onsemi.com>

DESCRIPTION AND PURPOSE:

This is a Final Process Change Notification to announce the transfer of products from Sanyo wafer fabrication sites located in Gunma and Gifu Japan to the waferfab Advanced Microelectronic Products, Inc(AMPI).

The product design and electrical specifications will remain identical. A full electrical characterization over the temperature range will be performed for each product to check the device functionality and electrical specifications. Qualification tests are designed to show that the reliability of transferred devices will continue to meet or exceed ON Semiconductor standards.



FINAL PRODUCT/PROCESS CHANGE NOTIFICATION # 16790EC

RELIABILITY DATA SUMMARY

Group EC

Test:	Conditions:	Interval:	Results
Steady State Operating Life	Tj=150degC	1000 hrs	Pass
High Temperature Reverse Bias	Ta=150degC, VDSS=max	1000 hrs	Pass
Temp Humidity Storage	Ta=85degC, RH=85%	1000 hrs	Pass
Temperature Cycle	Ta=-55degC to 150degC 30min each	100 cycles	Pass
Pressure Cooker	Ta=121degC, 2.03×10 ⁵ Pa, 100%	50 hrs	Pass
High Temperature Storage	Ta=150degC	1000 hrs	Pass
Low Temperature Storage	Ta=-55degC	1000 hrs	Pass
Solder Test	Ta=260degC±5degC,	10 s	Pass

Notice) ※1 Pre-treatment: Resistance to Soldering heat (Flow:260degC/10s)

ELECTRICAL CHARACTERISTIC SUMMARY

There is no change in the electrical performance. Datasheet specifications remain unchanged.

CHANGED PART IDENTIFICATION

No change to current part marking will occur. Marking traceability codes will be able to identify wafer fab die source.

List of affected Generic parts:

Group EC

PART_ID
MCH6321-TL-E
MCH3377-S-TL-E